

**Description:**

Vibracoustics Ltd Rail Mountings are rubber to metal bonded sandwich mounts manufactured as standard in 2m lengths. Available with double sided or one sided metal plates in various thicknesses and manufactured in both mild steel and stainless steel the mounts offer great flexibility.

Custom sizes and bespoke products are available to meet all your design requirements, please see our website for more information.



**Typical Applications Include:**

- Heavy industrial machinery.
- Drive elements.
- Construction equipment.
- Maritime applications.
- Ship constructions.
- Quarry and mining applications.

Part No.	Dimensions (mm)			
	Width	Height	Length	Top and Bottom Metal Thickness
VS64005	40	20	2000	5
VS64006	40	25	2000	5
VS64007	40	30	2000	5
VS64008	40	35	2000	5
VS64009	40	40	2000	5
VS64010	40	45	2000	5
VS64011	40	50	2000	5
VS64012	50	25	2000	5
VS64013	50	30	2000	5
VS64014	50	35	2000	5
VS64015	50	40	2000	5
VS64016	50	45	2000	5
VS64017	50	50	2000	5
VS64018	50	55	2000	5
VS64019	50	60	2000	5
VS64020	50	70	2000	5
VS64021	60	30	2000	5
VS64022	60	35	2000	5
VS64023	60	40	2000	5
VS64024	60	50	2000	5
VS64025	60	60	2000	5
VS64026	70	30	2000	5
VS64027	70	40	2000	5
VS64028	70	45	2000	5
VS64029	70	50	2000	5

Top and bottom metal thicknesses are included in height value.



Vibracoustics is continually seeking to improve products and reserves the right to change designs and specifications without prior notice or alteration of literature.

For applications and technical assistance please contact [Vibracoustics](http://www.vibracoustics.com), see index Ref 00-A-01

